

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

LIQUID CRYSTAL DISPLAY ELEMENT AND ITS PRODUCTION

Patent Number: JP11133438
Publication date: 1999-05-21
Inventor(s): MIYATA SHINICHI; TANAKA YOSHINORI; YAMAZAKI ATSUSHI
Applicant(s): MATSUSHITA ELECTRIC IND CO LTD
Requested Patent: ☐ JP11133438
Application Number: JP19970309669 19971024
Priority Number(s):
IPC Classification: G02F1/1339 ; G02F1/1339 ; G09F9/30
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To maintain the spraying uniformity of spacers, to enhance adhesion property between substrates and to improve a display grade by using ferromagnetic spacers and using magnetic field for holding the ferromagnetic spacers between glass substrates.
SOLUTION: The glass substrates with ITO electrodes are used for the substrate A and the substrate B and the ferromagnetic material spacers C are used for the spacers. The spacers C are sprayed by using a dry process spraying device by nitrogen blow. An acrylic resin material is used for an end-sealing material D. Further, the uniform magnetic field by a solenoid device is applied to the magnetic field F. The substrate A and the substrate B are bonded to each other by the end-sealing material D of an acrylic resin material within the magnetic field F, by which the ferromagnetic material spacers C are uniformly dispersed to the prescribed positions without movement between the substrate A and the substrate B. As a result, the spacing between the substrate A and the substrate B is made uniform and the execution of the uniform display is made possible.

Data supplied from the esp@cenet database - I2

【図3】

